



NO LEAD "ALL WEATHER" PIPE WRAP TAPE

Applications:

Boshart's "All Weather" Pipe Wrap Tape gives a uniform protective coating against abrasion and corrosive action for steel pipe, fittings and electrical conduit systems. It provides a physical barrier that is moisture proof, inert and non-conducting. Whether you are protecting metal piping/mill coated pipe systems above or below ground, overhead piping/electrical conduit and fittings in industrial applications, this tough PVC plastic tape with high tack adhesive resists corrosive action by salt water, soil acids, alkalis and salts.

Specifications & Industry Listings:

- Can be used on all types of pipe and fittings, including steel, galvanized, electrical conduit, cast and ductile iron.
- Black Pipe Wrap tape is listed by the International Association of Plumbing & Mechanical Officials (IAPMO) and carries the shield. Only Boshart's PW2-10NL black pipe wrap tape is tested to ASTM D-1000 standard.
- Provides excellent insulating capacities and superior abrasion resistance
- Resists/reduces corrosion problems caused by salts, salt water, soil acids and alkalis.
- Provides a dielectric barrier, prevents dielectric corrosion between buried steel pipe and soil minerals.
- Resists common chemicals and chemical vapors and protects against fungus and bacteria in many applications.
- Highly conformable remains pliable in a wide range of temperature and working environments, resists the effects of outdoor weathering and sunlight exposure.

Physical Properties:

Width: 2.0"
 Thickness: 10 mils (0.25mm)
 Length: 100 ft.
 Tensile Strength: 19.84 lbs./in., 9 kgf/25mm (3.528 N/mm)
 Elongation At Break: 200 %
 Adhesion to Steel: 19.75 oz./in., 0.56 kgf/25mm (0.219 N/mm)
 Operating Temperature: 15°F to 176°F (-10°C to 80°C)



UPC Listed

Part No.	Description	Case
PW2-10NL	BLACK - Width 2" x 100 ft. x Thickness 10 MIL (0.25mm)	24
PW2-G10NL	GREEN - Width 2" x 100 ft. x Thickness 10 MIL (0.25mm)	24



COMMITTED TO EXCELLENCE SINCE 1955

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com

BII ELECTRICAL TAPE

NO LEAD ELECTRICAL TAPE

- General all purpose black plastic vinyl tape
- Rated for continuous operation in temperature range of 14F to 176F(-10C to 80C)
- CSA Standard C22.2 No. 0 & 197 Certified
- UL Standard 570 Certified

Part No.	Description	Temp. Range	Quantity	
			Carton	Case
ETAWNL	General Purpose Vinyl Plastic Electrical Tape 0.18 mm x 19 mm x 18.3 m 7 mil x 3/4" x 60	-10°C to 80°C 14°F to 176°F	10	200



NO LEAD COLD & SUNLIGHT RESISTANT TAPE

- For use as electrical insulation on joints and splices in wires and cables, protective outer jacket, harness wrapping and protective conduits
- Low temperature application
- Resists abrasion, alkalis, acids, oil, solvents & corrosive chemicals
- Resists ultraviolet rays & moisture
- Flame retardant
- Plastic backing & aggressive rubber-resin adhesive
- Moisture tight electrical and mechanical protection
- CSA Standard C22.2 No. 0 & 197 Certified
- UL Standard 570 Certified

Part No.	Description	Temp. Range	Quantity	
			Carton	Case
ETCWNL	All Weather Vinyl Plastic 8 mil x 3/4" x 60	-18°C to 80°C 0°F to 176°F	10	200



SELF BONDING ELECTRICAL TAPE

- A conformable self-fusing rubber electrical insulating tape
- Designed for low voltage electrical insulating and moisture sealing applications
- Compatible with solid dielectric cable insulations
- Flexible over a wide temperature range
- CSA Standard C22.2 No. 0 & 197 Certified
- UL Standard 570 Certified

Part No.	Description	Temp. Range	Quantity	
			Carton	Case
ETSBR	Self Fusing Rubber Splicing Tape 3/4" x 22 ft. x 30 mil	-10°C to 80°C 14°F to 176°F	10	50



Recommendation:
Templex Rubber Splicing Tape should be overwrapped for mechanical protection with two half-lapped layers of either 3M vinyl electrical tape or cotton friction tape.



COMMITTED TO EXCELLENCE SINCE 1955

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com